

# Basic 7

## Make

EECS 201 Fall 2020

### Submission Instructions

This assignment will be submitted as a repository on the [UMich GitLab server](#). Create a Project on it with the name/path `eeecs201-basic7` and add `brng` as a Reporter.

### Preface

In this assignment you'll be provided yet another zipped archive containing some starter files.

```
$ wget https://www.eecs.umich.edu/courses/eeecs201/files/assignments/basic7.tar.gz
```

Initialize a Git repository inside of the extracted `basic7` directory. Create a file called `report.txt` in this directory. Add all of the present files and commit them.

Create a **private** project named `eeecs201-basic7` on the UMich GitLab ([gitlab.umich.edu](https://gitlab.umich.edu)) and add the instructor `brng` as a **Reporter**. Set this UMich GitLab project as your remote: you'll be pushing to it in order to submit.

In this assignment you will be incrementally building up more complex Makefiles. First, we'll start at the beginning.

## 1 A fresh start

1. `cd` into the `1` directory.
2. Create a file named `Makefile`.
3. Create a rule with a target called `all` that has this for a recipe:  

```
gcc -o nocat nocat.c
```
4. Create a rule with target called `clean` that has this for a recipe:  

```
rm -f nocat
```
5. Move the `all` rule so that it'll run by default when `make` is run without a target specified.
6. Make sure that your Makefile works correctly.
7. Add and commit `Makefile`.

## 2 Phonies

1. `cd` into the `2` directory.
2. Take a look at the Makefile and note the existing rules.
3. Try running `make all`, `make clean`, and `make test`.
4. Note that their recipes do not run.
5. Fix the Makefile so that each of the rules can run their recipes.

### 3 Dependencies

1. `cd` into the `3` directory.
2. Take a look at the Makefile. Note what each target in the Makefile requires which file.
3. Edit the Makefile so that each target has the proper dependencies. The one way to test this is to run `$ make clean` to delete any intermediate build files, and then run `$ make <some target>` then build one of the targets. The build should succeed as Make will proceed to build any missing intermediate files.

### 4 Not repeating yourself

1. `cd` into the `4` directory.
2. Create a file named `Makefile`.
3. Edit the `Makefile` so that:
  - It has a `CC` variable that is set to `gcc`  
This variable represents which C compiler to use.
  - It has a `BIN` variable that is set to `sum30`  
This variable represents what the output executable binary is named.
  - It has a `SRCS` variable that contains all the `.c` files under the `src` directory. This list should not be hardcoded: if a new `.c` file is added, the Makefile should not have to be edited to include it.
  - It has a rule to build the output executable binary. Don't worry about object code. Note that the `-o` flag for `gcc` sets the output name. This rule should have `SRCS` as a prerequisite. In addition, the recipe should make use of existing variables and **automatic variables** that refer to the target and prerequisites to avoid repeating yourself (e.g. you shouldn't be referring to `SRCS` or `BIN` in the compilation command).
  - There is a phony `all` target that builds the output executable binary.
  - There is a phony `clean` target that removes the output executable binary.
  - The `all` target should run when `$ make` is run (without a target specified).

### 5 Conclusion

1. Add and commit any changes you intend to submit.
2. Fill out the `REPORT` file in the following steps:
3. On the first line provide an integer time in minutes of how long it took for you to complete this assignment. It should just be an integer: no letters or words.
4. On the second line and beyond, write down what you learned while doing this assignment. If you already knew how to do all of this, put down "N/A".
5. Commit your `REPORT` file and push your commits to your remote.